

AGRIMAXFACTOR - Tekniska specifikationer



Description

AGRIMAXFACTOR är BKT:s helt nya 70-serie för traktorer som passar perfekt både för transport- och jordbearbetningsbruk. Det förbättrade däckmönstret med ännu längre däckklackar och ändrad däckklackriktning står för bättre vägegenskaper. Den minskade däckklackvinkeln säkerställer lägre rullningsmotstånd medan kontaktytan mot marken som utökats med 5 % betydligt minskar det upplevda bullret i hytten – båda dessa funktioner står för ökad komfort. Dessutom ger det kraftfulla polyesterhöljet extraordinär lateral stabilitet och snabbare styrningsrespons även vid användning vid hög hastighet eller tung last. Däcket har utmärkta bromsresultat på våta ytor.

Kort sagt utgörs AGRIMAXFACTORs övergripande fördelar av god hantering i kombination med i flera avseenden extraordinär förarkomfort samt utmärkt hållbarhet – allt detta är särskilda krav för allt tyngre maskiner inklusive de tyngre vikterna hos elektriska fordons batteripaket. Den exklusiva sidoväggen visar den perfekt inriktade "E-READY"-logotypen som visar BKT:s engagemang för elektrisk rörlighet.

UM

US Standard

Construction

 RADIAL

Machinery

Lantbruk: Traktor

Version	STANDARD
Type	TL
Tyre Size	360/70 R 24
LI/SS	122 D/125 A8

Dimensions US Standard

Usa code	94513659
Section Width (inch)	14.1
Overall Diameter (inch)	44.9
Static Loaded Radius (inch)	20.6
Rolling Circumference (inch)	133.3
Rim Rec	W 11
Rim Alt	W 10 ; W 12
ECE	E11-106R-0010946
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23
40	1820	2120	2410	2710	3010	3310
30	1920	2230	2540	2850	3160	3470
25	2000	2330	2660	2980	3310	3630
15	2090	2440	2780	3120	3460	3800
5 LT	2450	2840	3240	3640	4030	4430
5 HT	2090	2440	2780	3120	3460	3800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 3/29/2025 9:43 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..