

AS 2001 - Tekniska specifikationer



Description

AS 2001 är ett diagonalt korskiktsdäck som passar bäst till traktorer som används till jordbearbetning. Designen ger utmärkt dragförmåga och självrensande egenskaper. AS 2001 är tillverkat av en gummiblandning som är särskilt motståndskraftig mot skärande underlag och punkteringar och ger utmärkt lastkapacitet.

UM

International Standard

Construction

 BIAS

Machinery

Lantbruk: Traktor

Version	STANDARD
Type	TT
Tyre Size	9.5 - 22
LI/SS	110 A6

Dimensions International Standard

Ply Rating	8
Section Width (mm)	243
Overall Diameter (mm)	1007
Static Loaded Radius (mm)	470
Rolling Circumference (mm)	3074
Rim Rec	W 8
Rim Alt	W 7
ECE	E11-106R-0010508
TRA Code	R1

Load capacity (Kg)

km/h / bar	3.00
30	1060

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/2/2025 2:12 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..