

EARTHMAX SR 36 - Tekniska specifikationer



Description

EARTHMAX SR 36 (E3***) är ett radialdäck helt i stål som är specialkonstruerat för dumprar som används inom gruvdrift, stenbrott, skogsavverkning och transport. Det oriktade slitbanemönstret ger utmärkt grepp och stabilitet i alla typer av terräng, särskilt på våta, sumpiga och leriga underlag. Den öppna slitbanedesignen säkerställer också utmärkta självrengörande egenskaper som är avgörande för en smidig övergång mellan olika typer av ytor under transport.

EARTHMAX SR 36 är ett trestjärnigt däck som har extraordinär lastkapacitet utöver ett högt TKPH-värde (tonkilometer per timme) med betoning på förbättrad uthållighet och drifteffektivitet. Detta gör EARTHMAX SR 36 till ett perfekt val för tunga laster och långdistanstransporter. Dessutom ger det specialutvecklade mönstret och konstruktionen helt i stål utmärkt punkterings- och slitstyrka samt bästa möjliga övergripande däckhållbarhet.

UM

International Standard

Construction

 RADIAL

Machinery

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	14.00 R 24
LI/SS	171 B

Dimensions International Standard

TKPH	118
Overall Width (mm)	385
Overall Diameter (mm)	1360
Static Loaded Radius (mm)	627
Rolling Circumference (mm)	4161
Rim Rec	10.00W
Rim Alt	--
Star Rating	***
TRA Code	E3

Load capacity (Kg)

km/h / bar	7.00	8.00
50	5800	6150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 1/22/2025 5:32 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..