

## EARTHMAX SR 431 - Tekniska specifikationer



### Description

EARTHMAX SR 431 (E-4) är ett däck helt i stål, specialdesignat för anläggningsbilar som körs i krävande gruvmiljöer (dagbrott och underjordiska gruvor). Det oriktade mönstret säkerställer utmärkt dragförmåga och stabilitet i all möjlig terräng. Däcket har ett starkt hölje helt i stål och en speciell gummiblandning som gör det utomordentligt skär- och punkteringsbeständigt, med lång hållbarhet även i steniga, slitiga och krävande miljöer.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Stel dumper

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	16.00 R 25
LI/SS	183 B

## Dimensions US Standard

Usa code	94073603
TMPH	114
Overall Width (inch)	17.8
Overall Diameter (inch)	60.3
Static Loaded Radius (inch)	28.1
Rolling Circumference (inch)	183
Rim Rec	11.25/2.0
Star Rating	***
TRA Code	E4
Tread Depth	57

## Load capacity (lbs)

mph / psi	109	116	123	131
30	16500	17600	18200	19300

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 2/5/2025 9:23 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..