

EARTHMAX SR 459 - Tekniska specifikationer



Description

EARTHMAX SR 459 är ett radialdäck helt i stål för stela dumprar som arbetar i stenbrott och dagbrott. Den speciellt utvecklade symmetriska designen gör det möjligt att montera den på både bak- och framaxeln. EARTHMAX SR 459 är utformad för att säkerställa utmärkt hållbarhet och utmärker sig för sitt utomordentligt stora mönsterdjup (det största bland alla BKT-däck i denna storlek) i kombination med flerskiktiga stålbalten som ger överlägset skydd mot stötar och steninträngning. Det exceptionella mönsterdjupet säkerställer optimalt skydd för stommen utan att kompromissa med TKPH-värdena för en lång livslängd för däcket. Dessutom maximerar den slutna konstruktionen med flera nabbar markkontakten, vilket resulterar i utmärkt hantering och stabilitet samt utmärkt förarkomfort. EARTHMAX SR 459 utmärker sig för utmärkt grepp på alla underlag, även på leriga ytor.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Rigid Dumper • Stel dumper

Version	STANDARD COMPOUND
Type	TL
Tyre Size	27.00 R 49
LI/SS	223 B

Dimensions US Standard

Usa code	94513062
TMPH	325
Overall Width (inch)	29.4
Overall Diameter (inch)	107.1
Static Loaded Radius (inch)	48.5
Rolling Circumference (inch)	324.6
Rim Rec	19.50/4.0
Rim Alt	-
Star Rating	**
TRA Code	E4
Tread Depth	102

Load capacity (lbs)

mph / psi	73	76	80	83	87	91	94	98	102
30	45400	48100	49400	50700	52000	55100	56800	58400	60000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 2/23/2025 6:47 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..