

FARM 2000 - Tekniska specifikationer



Description

Däcket FARM 2000 är lämpligt på traktorer för markbearbetning. Det har designats med en speciell skär- och flisbeständig sammansättning för att säkerställa bättre hållbarhet. Tack vare sitt starka hölje erbjuder FARM 2000 en hög lastkapacitet. Det tillhandahåller också bra dragkrafter och självrengörande egenskaper.

UM

US Standard

Construction

 BIAS

Machinery

Lantbruk: Traktor

Version	SPECIAL
Type	TT
Tyre Size	12.4 - 28
LI/SS	122 A8

Dimensions US Standard

Usa code	94063871
Ply Rating	12
Section Width (inch)	12.6
Overall Diameter (inch)	50.7
Static Loaded Radius (inch)	23.7
Rolling Circumference (inch)	156.3
Rim Rec	W 11
Rim Alt	W 9 ; W 10
ECE	E11-106R-005965
TRA Code	R1

Load capacity (lbs)

mph / psi	36
25	3300

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 2/5/2025 10:31 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..