

FL 639 - Tekniska specifikationer



Description

FL 639 är ett flotationsradialdäck avsett för åkern, som även kan användas till spridningsarbeten. Det breda avtrycksområdet är en garanti för liten jordpackning, vilket leder till ökad produktivitet på åkern. Den förstärkta vulsten och skydd i sidoväggen bidrar till längre livslängd. FL 639 har extraordinär dragförmåga och erbjuder imponerande självrensande egenskaper.

UM

International Standard

Construction

 RADIAL

Machinery

Lantbruk: Spridare

| | |
|-----------|---------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 800/40 R 22.5 |
| LI/SS | 168D/178A8 |

Dimensions International Standard

| | |
|----------------------------|------------------|
| Section Width (mm) | 828 |
| Overall Diameter (mm) | 1212 |
| Static Loaded Radius (mm) | 538 |
| Rolling Circumference (mm) | 3642 |
| SRI (mm) | 575 |
| Rim Rec | AG 28.00 |
| ECE | E11-106R-0010830 |

Load capacity (Kg)

| km/h / bar | 0.8 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 |
|------------|------|------|------|------|------|------|------|------|-------|
| 70 | 1635 | 2095 | 2605 | 2960 | 3420 | 3880 | 4235 | 4645 | 5100 |
| 65 | 1795 | 2300 | 2860 | 3250 | 3755 | 4260 | 4650 | 5100 | 5600 |
| 50 | 2170 | 2780 | 3460 | 3935 | 4545 | 5155 | 5630 | 6170 | 6780 |
| 40 | 2400 | 3075 | 3825 | 4350 | 5025 | 5700 | 6225 | 6825 | 7500 |
| 30 | 2710 | 3470 | 4315 | 4910 | 5670 | 6430 | 7025 | 7700 | 8460 |
| 25 | 2835 | 3630 | 4515 | 5135 | 5930 | 6730 | 7350 | 8055 | 8850 |
| 10 | 3230 | 4135 | 5145 | 5850 | 6755 | 7665 | 8370 | 9175 | 10080 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 2/22/2025 8:47 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..