

MULTIMAX MP 529 - Tekniska specifikationer



Description

MULTIMAX MP 529 är ett flerk Funktionsradialdäck med stålbelte designat för teleskoplastare inom industriella tillämpningar. Mönsterdesignen har tagits fram speciellt för hårda underlag. Den starka sidoväggen och ett större avtryck ger enastående stabilitet i lyftläget. MULTIMAX MP 529 är tillverkat med ett starkt hölje och en speciell gummblandning som gör det utomordentligt skär- och punkteringsbeständigt, med exceptionell hållbarhet och lång livslängd.

UM

US Standard

Construction

 RADIAL

Machinery

Industri: Teleskoplastare

Version	STEEL BELTED
Type	TL
Tyre Size	400/70 R 20 IND (405/70R20)
LI/SS	149 A8/B

Dimensions US Standard

Usa code	94512737
Section Width (inch)	16.3
Overall Diameter (inch)	42.9
Static Loaded Radius (inch)	19.7
Rolling Circumference (inch)	130.5
Rim Rec	13
Rim Alt	12 SDC;13SDC;14
ECE	E11-106R-0010769

Load capacity (lbs)

mph / psi	23	29	35	41	46	52	58	61	64
30	3420	4020	4630	5240	5840	6500	7160	-	-
25	3420	4020	4630	5240	5840	6500	7160	-	-
20	3660	4320	4990	5670	6330	7000	7670	-	-
15	3810	4500	5190	5890	6570	7260	7960	-	-
5 Cyc.	4210	5150	6080	7010	7950	8880	9820	10300	10760
Static	6460	7890	9330	10760	12190	13620	15060	15770	16490

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 1/22/2025 5:31 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..