

PORTMAX PM 93 PLUS - Tekniska specifikationer



Description

PORTMAX PM 93 PLUS är specialdesignat för grensletruckar som används i hanteringsverksamhet med hamncontainrar. Det är ett radialdäck helt i stål och stålbältet med flera lager stål ger fantastisk stabilitet och hållbarhet. Den speciella, antistatiska gummiblandningen ger särskilt hög motståndskraft mot värme och längre livslängd. PORTMAX PM 93 PLUS erbjuder lägre rullningsmotstånd för bättre bränsleekonomi.

UM

US Standard

Construction

 RADIAL

Machinery

Industri: Grensletruck

Version	INDUSTRIAL
Type	TL
Tyre Size	480/95 R25
LI/SS	208 A5

Dimensions US Standard

Usa code	94513222
Overall Width (inch)	18.5
Overall Diameter (inch)	61.2
Static Loaded Radius (inch)	27.7
Rolling Circumference (inch)	185.7
Rim Rec	13.00/2.5
Star Rating	***

Load capacity (lbs)

mph / psi	145
15	39700

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 1/22/2025 5:07 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..