

## TR 678 - Tekniska specifikationer



### Description

TR 678 är särskilt konstruerat för skogsbruk. Den robusta däckklacksdesignen ger utmärkt dragförmåga och självrensande egenskaper. Däckhöljets starka struktur ger hög lastkapacitet, och stålbelten skyddar däcket från punkteringar och skador. TR 678 är tillverkat av en skärbeständig gummiblandning som ger utmärkt motståndskraft mot skärande underlag och punkteringar även i svår terräng och under extrema förhållanden.

### UM

International Standard

### Construction

 BIAS

### Machinery

Lantbruk: Arbetsfordon • Släpvagn  
Industri: Grävmaskin • Släpvagn

Version	STEEL BELTED
Type	TL
Tyre Size	710/45 - 26.5
LI/SS	180 A2 / 173 A8

## Dimensions International Standard

Ply Rating	24
Section Width (mm)	705
Overall Diameter (mm)	1345
Rim Rec	AG 24.00
ECE	E11-106R-008292
TRA Code	LS2

## Load capacity (Kg)

km/h / bar	6.00
40	6500
10	8000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12/26/2024 10:45 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..