

## SKID POWER - Teknik Özellikler



### Description

SKID POWER inşaat uygulamalarında kullanılan nokta dönüşlü yükleyiciler için tasarlanmıştır. Sıra dışı kendini temizleme özelliklerinin yanı sıra, kusursuz çekiş gücüne sahiptir. Lastik, ekstra derin desene ve kesilme ve parçalanmaya karşı yüksek dayanıklılık ve olağanüstü sağlamlık sağlayan yanak korumasına sahiptir. SKID POWER gevşek yüzeyler için ideal lastiktir.

### UM

US Standard

### Construction

 BIAS

### Machinery

Endüstriyel: Mini yükleyici

Version	IMPLEMENT
Type	TL
Tyre Size	23 X 10.5 - 12
LI/SS DRIVE WHEEL	90 A8
LI/SS FREE ROLLING	90 A8

## Dimensions US Standard

Usa code	94076093
Ply Rating	6
Section Width (inch)	10.4
Overall Diameter (inch)	23.2
Rim Rec	8.5 I - 55
Rim Alt	7.00 I - 55 ; I - 70 ; I - 90
ECE	E11-106R-008809

## Load capacity (lbs)

mph / psi	41
25 FR	1320
25 DW	1320

Printed on 7/27/2024 1:34 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..