

AGRIMAX PROHARVEST - Technical Specifications



Description

AGRIMAX PROHARVEST is BKT's response to the current market needs in terms of combines and harvesting machines. The advanced VF (Very High Flexion) technology allows AGRIMAX PROHARVEST to carry 40% more load compared to standard tires with the same tire pressure minimizing soil compaction. Moreover, the three layers of steel belts combined with the cut and chip resistant compound ensure excellent puncture resistance, even on case of stubbles or crops leftovers on the field. The structure of the tire with a reinforced bead and a strong polyester carcass is synonym of durability and stability of the tire even during heavy duty operation. The tire casing, engineered to guarantee high load capacity, combined with the CFO (Cyclic Field Operation) technology allows AGRIMAX PROHARVEST to handle temporary overloads during operations like harvesting, reducing stress and wear on the tire. Once the load is reduced, the tire returns to its standard operating condition, thus extending its service life and improving operational efficiency. The open shoulder design improves traction on rough and wet terrain while facilitating the ejection of mud and debris, ensuring smooth transitions from field to road and enhancing safety. On the field and on the road AGRIMAX PROHARVEST can reach up to 65km/h making your transit operation easier and faster thus improving overall productivity.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Harvester

Version

STEEL BELTED

Type

TL

Tyre Size	VF800/70 R 32
-----------	---------------

LI/SS	187 D
-------	-------

Dimensions US Standard

Usa code	94512263
----------	----------

Section Width (inch)	31.7
----------------------	------

Overall Diameter (inch)	76.1
-------------------------	------

Static Loaded Radius (inch)	33.3
-----------------------------	------

Rolling Circumference (inch)	229
------------------------------	-----

Rim Rec	DW 28 B
---------	---------

ECE	E11-106R-0010664
-----	------------------

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
45	9180	10550	12110	13680	15240	16810	18370	19550
from 40 to 25	10100	11610	13330	15050	16770	18480	20200	21490
20	10300	11840	13590	15340	17100	18850	20600	21920
12	10500	12070	13860	15640	17430	19220	21010	22350
5	11110	12760	14650	16540	18440	20330	22220	23640
Upto 20 Cyc	11460	13170	15120	17070	19020	20980	22930	24390
Upto 10 Cyc	13680	15720	18050	20380	22710	25040	27370	29120
Upto 5 Cyc	14990	17230	19770	22330	24890	27440	29990	31910
10HT	10300	11840	13590	15340	17100	18850	20600	21920

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 1/9/2025 12:32 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..