

AGRIMAX TURF RT 333 - Technical Specifications



Description

AGRIMAX TURF RT 333 (R-3+) is a radial tire designed for small tractors in gardening, vineyards and orchards applications. Its rounded shoulder design provides low soil compaction and makes it extremely delicate on the ground. Its unique extra-deep tread (R-3+) and the special design with directional blocks stand for excellent traction both in the field and on the road, and an extended tire life cycle. AGRIMAX TURF RT 333 (R-3+) ensures great self-cleaning properties and thanks to its low rolling resistance, allows for significant fuel saving.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Orchard Harvester • Small Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	340/85 R 28
LI/SS	127 A8 / 127 B

Dimensions US Standard

Usa code	94076390
Section Width (inch)	14.6
Overall Diameter (inch)	50.7
Static Loaded Radius (inch)	23
Rolling Circumference (inch)	152.5
Rim Rec	W 12
Rim Alt	W11;DW11;DW12
ECE	E11-106R-0010343

Load capacity (lbs)

mph / psi	9	12	15	17	20	23
30	2130	2470	2830	3170	3520	3860
25	2130	2470	2830	3170	3520	3860
20	2290	2650	3030	3400	3770	4140
5 LT	2850	3320	3790	4250	4710	5170
5 HT	2290	2650	3030	3400	3770	4140

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 11/21/2024 9:22 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..