

# AGRIMAX TURF RT 333 - Technical Specifications



## Description

AGRIMAX TURF RT 333 (R-3+) is a radial tire designed for small tractors in gardening, vineyards and orchards applications. Its rounded shoulder design provides low soil compaction and makes it extremely delicate on the ground. Its unique extra-deep tread (R-3+) and the special design with directional blocks stand for excellent traction both in the field and on the road, and an extended tire life cycle. AGRIMAX TURF RT 333 (R-3+) ensures great self-cleaning properties and thanks to its low rolling resistance, allows for significant fuel saving.

## UM

International Standard

## Construction

 RADIAL

## Machinery

Agriculture: Orchard Harvester • Small Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	420/85 R 24
LI/SS	137 A8 / 137 B

## Dimensions International Standard

Section Width (mm)	435
Overall Diameter (mm)	1324
Static Loaded Radius (mm)	594
Rolling Circumference (mm)	3957
SRI (mm)	625
Rim Rec	W 15 L
Rim Alt	DW15L;DW14L
ECE	E11-106R-0010344

## Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	1265	1475	1680	1890	2095	2300
40	1265	1475	1680	1890	2095	2300
30	1360	1580	1800	2025	2245	2465
10 LT	1700	1975	2255	2530	2810	3085
10 HT	1360	1580	1800	2025	2245	2465

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 11/21/2024 9:22 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..