

# **AGRIMAX TURF RT 333 - Technical Specifications**



### Description

AGRIMAX TURF RT 333 (R-3+) is a radial tire designed for small tractors in gardening, vineyards and orchards applications. Its rounded shoulder design provides low soil compaction and makes it extremely delicate on the ground. Its unique extra-deep tread (R-3+) and the special design with directional blocks stand for excellent traction both in the field and on the road, and an extended tire life cycle. AGRIMAX TURF RT 333 (R-3+) ensures great selfcleaning properties and thanks to its low rolling resistance, allows for significant fuel saving.

### UM

**US Standard** 

#### Construction

## Machinery

Agriculture: Orchard Harvester • Small Tractor • Vineyard Harvester

Version	STANDARD
Туре	TL
Tyre Size	420/85 R 24
LI/SS	137 A8 / 137 B

# **Dimensions US Standard**

Usa code	94501649
Section Width (inch)	17.1
Overall Diameter (inch)	52.1
Static Loaded Radius (inch)	23.4
Rolling Circumference (inch)	155.8
Rim Rec	W 15 L
Rim Alt	DW15L;DW14L
ECE	E11-106R-0010344

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23
30	2790	3260	3710	4170	4620	5080
25	2790	3260	3710	4170	4620	5080
20	3000	3490	3970	4470	4950	5440
5 LT	3750	4360	4980	5580	6200	6810
5 HT	3000	3490	3970	4470	4950	5440

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

#### Printed on 11/21/2024 10:20 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..