

EARTHMAX SR 36 - Technical Specifications



Description

EARTHMAX SR 36 (E3***) is an All-Steel radial tire specially designed for dump trucks operating in mining, quarry, logging, or haulage applications. The non- directional rock tread pattern provides excellent traction and stability on all types of terrains, especially on wet, boggy and muddy grounds. The open tread design also ensures excellent selfcleaning properties that are essential for a smooth transition between different types of surfaces during transport. EARTHMAX SR 36 is a three-star-rated tire that features extraordinary load capacity in addition to a high TKPH value (Tonne Kilometre per Hour) emphasizing improved endurance and operating efficiency. This makes EARTHMAX SR 36 a perfect choice for heavy loads and long-haul transports. Moreover, the specifically developed pattern and the All Steel construction provide excellent puncture and wear resistance as well as top overall tire durability.

UM

US Standard

Construction

🗱 RADIAL

Machinery

Version	CUT RESISTANT COMPOUND
Туре	TL
Tyre Size	14.00 R 24
LI/SS	171 B

Dimensions US Standard

Usa code	94512454
ТМРН	81
Overall Width (inch)	15.2
Overall Diameter (inch)	53.5
Static Loaded Radius (inch)	24.7
Rolling Circumference (inch)	163.8
Rim Rec	10.00W
Rim Alt	-
Star Rating	***
TRA Code	E3

Load capacity (lbs)

mph / psi	102	116
30	12800	13600

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 1/21/2025 5:01 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..