

EARTHMAX SR 468 - Technical Specifications



Description

EARTHMAX SR 468 is an All Steel radial tire specially designed for rigid haul trucks. Its unique tread design with special tread compounds makes it perfect for hard, rocky and tough mining conditions. Its tread lug blocks with circumferential grooves and intertwined blocks ensures effective heat dissipation. Also, the sturdy square shoulder assist in ejecting loose stones to protect the tire from injury. EARTHMAX SR 468 is developed using BKT's cutting-edge technology to carry heavy loads, deliver longer service life and provide resistance to rock cuts and punctures.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Rigid Dump Truck

Version	STANDARD COMPOUND
Type	TL
Tyre Size	27.00 R 49
LI/SS	223 B

Dimensions International Standard

TKPH	458
Overall Width (mm)	735
Overall Diameter (mm)	2720
Static Loaded Radius (mm)	1235
Rolling Circumference (mm)	8351
Rim Rec	19.50/4.0
Rim Alt	-
Star Rating	**
TRA Code	E4
Tread Depth	83.0

Load capacity (Kg)

km/h / bar	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00
50	20600	21800	22400	23000	23600	25000	25750	26500	27250

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12/22/2024 8:53 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..